In the Claims:

1. (Currently Amended) A method of voice optimization in a packet switched network, comprising:

initializing ~~default parameters for~~ end-point devices on a network, wherein the initializing comprises setting default parameters for the end-point devices with respect to choice of preferred CODEC, number of voice samples per packet, and jitter buffer size, and performing one or more tests to determine an optimum configuration for the end-point devices;

measuring performance parameters of the network external to the end-point devices; and

evaluating whether the measured performance parameters signify that a connection to the network is below a desired level of operation and, if so, adjusting the default parameters for the end-point devices based on the evaluating.

2. (Previously Presented) The method of claim 1, wherein the adjusting includes performing functions that are selected from a group consisting of re-negotiating a CODEC connection, re-setting of parameters for the packet size and re-setting the jitter buffer.

3. (Previously Presented) The method of claim 2, wherein the performance parameters being measured are selected from a group consisting of throughput, latency, packet loss, bandwidth, number of network hops to the end-point devices, round trip delay and any combination thereof.

4. (Previously Presented) The method of claim 3, wherein the measuring is performed with at least one tool selected from a group consisting of a ping tool, a network trace tool and a packet loss measurement tool.

5. (Previously Presented) The method of claim 1, wherein the performance parameters being measured are selected from a group consisting of throughput, latency and packet loss, bandwidth, number of network hops to the end-point devices, round trip delay, and any combination thereof.

6.   (Previously Presented) The method of claim 5, wherein the measurements are obtained from measuring with at least one tool selected from a group consisting of a ping tool, a network trace tool and a packet loss measurement tool.

7.   (Previously Presented) The method of claim 1, wherein the adjusting is manually initiated by a user.

8.   (Previously Presented) The method of claim 2, wherein the adjusting is manually initiated by a user.

9.   (Previously Presented) The method of claim 1, further comprising registering the end-point devices with a private branch exchange (PBX) on the network, wherein said PBX measures performance parameters between the PBX and the end-point to determine the default parameters.

10.   (Previously Presented) The method of claim 1, further comprising:
        measuring and evaluating existing performance parameters with respect to quality of connection, the initializing being based on the evaluating.

11.   (Previously Presented) The method of claim 10, wherein the existing performance parameters being measured are selected from a group consisting of throughput, latency, packet loss, bandwidth, number of network hops to the end-point devices, round trip delay and any combination thereof.

12.   (Previously Presented) The method of claim 1, further comprising evaluating the measured performance parameters with respect to quality of connection and performing the adjusting as a result of the evaluating.

13.   (Previously Presented) The method of claim 1, wherein the adjusting is carried out during transmission of media to the end-point devices.

14.   (Currently Amended) An apparatus to effect voice optimization in a packet switched network, comprising:

an initializer configured and arranged to initialize default parameters for end-point devices on a network with respect to choice of preferred CODEC, number of voice samples per packet, and jitter buffer size, and perform one or more tests to determine an optimum configuration for the end-point devices;

a measurer configured and arranged to measure performance parameters of the network external to the end-point devices;

an evaluator configured and arranged to make a determination as to whether the measured performance parameters signify that a connection to the network is below a desired level of operation; and

an adjuster configured and arranged to adjust the default parameters based upon the determination being that the measured performance parameters signify that the connection to the network is below the desired level of operation.

15.   (Previously Presented) The apparatus of claim 14, wherein the measurer includes software tools configured to measure the performance parameters, the performance parameters being selected from a group consisting of throughput, latency, packet loss, bandwidth, number of network hops to the end-point devices on the network, round trip delay and any combination thereof.

16.   (Previously Presented) The apparatus of claim 15, wherein the measurer includes software tools configured to measure the performance parameters, the software tools including at least one tool selected from a group consisting of a ping tool, a network trace tool and a packet loss measurement tool.

17.   (Previously Presented) The apparatus of claim 16, wherein the software tools include the at least one tool selected from the group consisting of the ping tool, the network trace tool and the packet loss measurement tool.

4

18. (Previously Presented) The apparatus of claim 14, wherein the adjuster is configured and arranged to perform functions which are selected from a group consisting of a re-negotiation of a CODEC connection and a re-set of the default parameters for the packet size and a re-set of the default parameters for the jitter buffer size.

19. (Previously Presented) The apparatus of claim 14, further comprising a private branch exchange (PBX) on the network; a register configured to register the end-point devices with the private branch exchange (PBX) on the network; and a controller responsive to the register completing registration of the end-point devices with the PBX to direct the initializer to initialize the default parameters.

20. (Currently Amended) An apparatus to effect voice optimization in a packet switched network, comprising:

      means for initializing default parameters for end-point devices on a network with respect to choice of preferred CODEC, number of voice samples per packet, and jitter buffer size, and performing one or more tests to determine an optimum configuration for the end-point devices;

      means for measuring performance parameters of the network external to the end-point devices;

      means for making a determination as to whether the measured performance parameters signify that a connection to the network is below a desired level of operation; and

      means for adjusting the default parameters based upon the determination being that the measured performance parameters signify that the connection to the network is below the desired level of operation.

21. (Previously Presented) The apparatus of claim 20, wherein the measuring means includes software tools configured to measure the performance parameters, the performance parameters being selected from a group consisting of throughput, latency, packet loss, bandwidth, number of network hops to the end-point devices on the network, round trip delay and any combination thereof.

22.   (Previously Presented) The apparatus of claim 20, wherein the measuring means includes software tools configured to measure the performance parameters, the software tools including at least one tool selected from a group consisting of a ping tool, a network trace tool and a packet loss measurement tool.

23.   (Previously Presented) The apparatus of claim 20, wherein the adjusting means includes means for re-negotiating a CODEC connection, means for re-setting the default parameters for the packet size and means for re-setting the default parameters for the jitter buffer size.

24.   (Previously Presented) The apparatus of claim 20, further comprising a private branch exchange (PBX) on the network; means for registering the end-point devices with the private branch exchange (PBX) on the network; and means responsive to the registering means completing registration of the end-point devices with the PBX for directing the initializing means to initialize the default parameters.